

MTP40S - AVAILABLE CONFIGURATIONS

SKU	DESCRIPTION
MTP40S-AU_B3-PV-LM-LI	FREQ. RANGE 510-698MHz,CERAMIC COATING,LEMO CONN. AU VERSION,LINEAR
MTP40S-EU_B2-BL-LM-LI	FREQ. RANGE 566-798MHz,50 mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EU_B2-PV-LM-LI	FREQ. RANGE 566-798MHz,50 mW,CERAMIC COATING, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EU_B3-BL-DP-LI	FREQ. RANGE 510-698MHz,50 mW,BLACK COLOR, DPA AUDIO CONNECTOR,LINEAR
MTP40S-EU_B3-BL-LM-LI	FREQ. RANGE 510-698MHz,50 mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EU_B3-PV-DP-LI	FREQ. RANGE 510-698MHz,50 mW,CERAMIC COATING, DPA AUDIO CONNECTOR,LINEAR
MTP40S-EU_B3-PV-LM-LI	FREQ. RANGE 510-698MHz,50 mW,CERAMIC COATING, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EU_B6-PV-LM-LI-NB	FREQ. RANGE 960-1160MHz, CERAMIC COATING, LEMO AUDIO CONNECTOR, LINEAR,NARROW BAND
MTP40S-EU_B7-BL-DP-LI	FREQ. RANGE 470-663MHz 100mW,BLACK COLOR, DPA AUDIO CONNECTOR,LINEAR
MTP40S-EU_B7-BL-LM-LI	FREQ. RANGE 470-663MHz 100mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EU_B7-BL-LM-LI-NB	FREQ. RANGE 470-663MHz 100mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR,NARROW BAND
MTP40S-EU_B7-PV-DP-LI	FREQ. RANGE 470-663MHz,50 mW,CERAMIC COATING, DPA AUDIO CONNECTOR,LINEAR
MTP40S-EU_B7-PV-LM-LI	FREQ. RANGE 470-663MHz,50 mW,CERAMIC COATING, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B2-BL-LM-LI	FREQ. RANGE 566-798MHz 100mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B2-PV-LM-LI	FREQ. RANGE 566-798MHz 100mW,CERAMIC COAT., LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B2-PV-LM-LI-NB	FREQ. RANGE 566-798MHz 100mW,CERAMIC COAT., LEMO AUDIO CONNECTOR,LINEAR,NARROW BAND
MTP40S-EUX_B3-BL-DP-LI	FREQ. RANGE 510-698MHz 100mW,BLACK COLOR, DPA AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B3-BL-LM-5K-LI	FREQ. RANGE 510-698MHz 100mW,50 mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR,5K OPTION
MTP40S-EUX_B3-BL-LM-LI	FREQ. RANGE 510-698MHz 100mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B3-PV-DP-LI	FREQ. RANGE 510-698MHz 100mW,CERAMIC COAT., DPA AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B3-PV-LM-LI	FREQ. RANGE 510-698MHz 100mW,CERAMIC COAT., LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B3-PV-LM-LI-5K	FREQ. RANGE 510-698MHz 100mW,CERAMIC COAT., LEMO AUDIO CONNECTOR,LINEAR,5K OPTION
MTP40S-EUX_B7-BL-LM-LI	FREQ. RANGE 470-663MHz 100mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B7-BL-LM-LI-NB	FREQ. RANGE 470-663MHz 100mW,BLACK COLOR, LEMO AUDIO CONNECTOR,LINEAR,NARROW BAND
MTP40S-EUX_B7-PV-DP-LI	FREQ. RANGE 470-663MHz 100mW,BLACK COLOR, DPA AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B7-PV-LM-LI	FREQ. RANGE 470-663MHz 100mW,CERAMIC COAT., LEMO AUDIO CONNECTOR,LINEAR
MTP40S-EUX_B7-PV-LM-LI-5K	FREQ. RANGE 470-663MHz 100mW,CERAMIC COAT., LEMO AUDIO CONNECTOR,LINEAR,5K OPTION
MTP40S-EUX_B7-PV-LM-LI-NB	FREQ. RANGE 470-663MHz 100mW,CERAMIC COAT., LEMO AUDIO CONNECTOR,LINEAR,NARROW BAND
MTP40S-JB_BP-BL-LM-NB-LI	FREQ. RANGE 806-810MHz, BLACK COLOR, LEMO AUDIO CONNECTOR, JP VERSION,LINEAR,NARROW BAND
MTP40S-JB_BP-PV-LM-NB-LI	FREQ. RANGE 806-810MHz, CERAMIC COATING, LEMO AUDIO CONNECTOR, JP VERSION,LINEAR,NARROW BAND
MTP40S-JP_B2-BL-LM-LI	FREQ. RANGE 566-798MHz,BLACK COLOR, LEMO AUDIO CONNECTOR, JP VERSION,LINEAR
MTP40S-JP_B2-PV-LM-LI	FREQ. RANGE 566-798MHz,CERAMIC COATING, LEMO AUDIO CONNECTOR, JP VERSION,LINEAR
MTP40S-MX_B2-BL-LM-LI	FREQ. RANGE 566-798MHz,BLACK COLOR, LEMO AUDIO CONNECTOR, MX VERSION,LINEAR
MTP40S-US8_B8-BL-LM-LI-NB	FREQ. RANGE 940-960MHz, BLACK COLOR, LEMO AUDIO CONNECTOR,USA VERSION,LINEAR,NARROW BAND
MTP40S-USX_B7-BL-LM-LI	FREQ. RANGE 470-663MHz,BLACK COLOR, LEMO AUDIO CONNECTOR, USX VERSION,LINEAR
MTP40S-USX_B7-BL-LM-LI-NB	FREQ. RANGE 470-663MHz,BLACK COLOR, LEMO AUDIO CONNECTOR, USX VERSION,LINEAR,NARROW BAND
MTP40S-USX_B7-PV-LM-LI	FREQ. RANGE 470-663MHz,CERAMIC COATING, LEMO AUDIO CONNECTOR, USX VERSION,LINEAR
MTP40S-USX_B7-PV-LM-LI-NB	FREQ. RANGE 470-663MHz,CERAMIC COATING, LEMO AUDIO CONNECTOR, USX VERSION,LINEAR,NARROW BAND