

MTP61 - Tree Menu (firmware v1.4.0)

BT sync			
PRESET	Load	U1--/U2--/DPA... /Factory	
	Save	U1--/U2--/DPA...	
	Active	Factory/...	
RF	Freq	Frequency/GR/CH	
	RF Power	OFF/10/10L/20/20L/50/100mW	
	Antenna	507/560...	
AUDIO	Gain	-40 to +26 dB	
	Ch. Mod.	Wide/Narrow	
	HPF	FLAT/45/60/80/120/170/240	
	Mic Mode	2W/2W+B/3W/AUX	
	PTT	Disabled/Mute/ON	
	Phase	0/180	
	Limiter	OFF/ON	
	Cal Tone	Cal. Tone	OFF/ON
		Frequency	1000 Hz /400 Hz
		Level	-20 dB
RECORDER	REC	OFF/ON	
	Elapsed	hh:mm:ss	
	Remaining	hh:mm:ss	
	Timecode	hh:mm:ss	
	Jam	Jam	OFF/Running
		Source	Wire/Tentacle
		TC	hh:mm:ss
		TC ext	hh:mm:ss
	TC setup	FPS	23.98/24/25/29.97/29.97DF/30/30DF/50/59.94/59.94DF/60
		Ubits	SMPT/mm.dd.yy/dd.mm.yy/mm.dd.yyyy/dd.mm.yyyy
		Time	hh:ss:mm
		Date	mm:dd:yyyy
	Bit Depth	24/32 bit	
		Name by	Sequence/Scene&Tk
	SD Card	Scene	1-99
Shot		none/A-Z	
Take		1-99	
Format		"warning..."	
SETTINGS	BT	Pwr	Yes/No
		Mode	Wisycom
		Pairing	Yes/No
		Passcode	Yes/No
		Reset Dev	...
	Name	Transmitter (8 char)	
	Battery	% / time	
	LED	Brightn.	OFF, from 1 to 5
		Mode	Full/Alarms/PTT
		Brightn.	from 1 to 5
	Display	LOW	from 5 to 60 sec
		OFF	from 10 to 120 sec (10 sec step) / OFF
		Direction	Up/Down
		Auto-lock	60 sec/30 sec/15 sec/OFF
	INFO	FW	Version
BL			v1.3.0
DSP			vX.Y
Serial		09900004	
Range		470-1075	
Band		B1	
HW		Country	US
		Main rev.	0:02
		Main opt.	1
		Options	...
Profile		US/EU/CA	
STD		depending on the country	
Battery		Level	90%
		Time	6h:47m%
		Voltage	3,79V
	Current	194mA	
	Temp	26 C	
Model	MTP61		
Alarms	0		